**DG** FAX 0769-87056205 FAX 0769-89026335

# XY axis Steel Extended Contact Slide Stages MLT32-60C Stage size G0mm

**RoHS** 

Application Systems

Machine Vision

Manual **Positions** 

Motion Control Products

Optical & Mirror Holder

FA Parts

Measurement &Control

FA Electrical Parts

Tool & Measure

Cleanroom & AntiStatic

Index

X Axis

Z Axis XZ Axis

XYZ Axis

Rotation

Goniomenters /Tilt

Multiaxis

Linear Guide

□15mm **□25mm** 

**□**40mm

□50mm

□70mm □80mm

□100mm

□120mm

Others

Hardened Steel linear stages with integrated bearing ways for superior stiffness, accuracy and durability.





















### Guide

- ▶ Stainless steel types (MLT32-60C) are available for superior corrosion resistance. Reference G064
- ▶The part number suffix FP indicates products with fine-pitch screws instead of standard micrometers.
- ▶ Fine Pitch screws have a screw pitch of 0.25mm and require a hex wrench or the optional hex wrench with knob (NSC) for adjustment. nce H010



### Attention

▶ Micrometer brackets may extend above the top surface of some stages. Check drawings for more information.

SPEC UP

Specification	ıs			
Table Size [mm]		60×60		
Travel [mm]		±6.5		
Positioning Slide		Extended contact ball guide		
Primary Material		Steel		
Finish		Super black chrome		
Load Capacity [N]		343 (35.0kgf)		
Travel Accuracy	Straightness [µm]	1		
	Pitch ["]	25		
	Yaw ["]	15		
Max. Moment Capacity	Pitch [N·m]	13.2		
	Roll [N·m]	13.2		
	Yaw [N·m]	9.8		
Moment Stiffness	Pitch ["/N·cm]	0.33		
	Roll ["/N·cm]	0.33		
	Yaw ["/N·cm]	0.32		
Parallelism [µm]		50		
Running Parallelism [µm]		20		


Part Number	MLT32-60C	MLT32-60CFP	MLT32-60S	MLT32-60SFP	MLT32-60SDM	MLT32-60SWP
Opposite Model	_	_	MLT32-60SR	MLT32-60SRFP	_	_
Micrometer Position	Center	Center	Side	Side	Side	Side
Lead of Actuator [mm/rotation]	0.5	0.25	0.5	0.25	Coarse: 0.5 Fine: 0.025	Coarse: 0.25 Fine: 0.005
Micrometer Readable Resolution [mm]	0.01	_	0.01	_	Coarse: 0.01 Fine: 0.0005	Coarse: 0.005 Fine: 0.0005
Weight [kg]	0.9	0.9	0.9	0.9	1.0	0.9










## **Outline Drawing**

























Application Systems

Machine Vision

### Manual **Positions**

Motion Control Products

Optical & Mirror Holder

FA Parts

Measurement &Control

FA Electrical Parts

Tool & Measure

Cleanroom & AntiStation

Index

X Axis

Z Axis

XZ Axis

XYZ Axis

Rotation

Goniomenters /Tilt

Multiaxis

Linear Guide

□15mm

 $\square$ 25mm

□40mm

□50mm

**□**60mm

□70mm

□80mm

□100mm

□120mm Others