


2/3" F2.8/12 C Mount

		Working distance			Optical Magnification		2/3" Field of View(mm)	
		mm					H	V
Focal Length		f=12mm						
Max Diameter (Ratio)		F=1:2.8~16			5000		0.002X	
Picture Size		2/3"(8.8x6.6mm)	1/2"(6.4x4.8mm)	1/3"(4.8x3.6mm)	2000	0.006X	364.7	273.7
Angle	H	39.8°	29.5°	22.3°	1000	0.012X	735.4	551.5
	V	30.4°	22.3°	16.8°	900	0.013X	662.7	497
	D	48.5°	36.4°	27.7°	800	0.015X	590	442.5
Object Dimension at 200mm	H	153.8mm	111.9mm	83.8mm	700	0.017X	517.4	388
	V	115.4mm	83.8mm	62.7mm	600	0.02X	444.7	306.3
	D	193.3mm	140.2mm	104.8mm	550	0.022X	408.4	306.3
Distortion (TV)		<0.2%	<0.1%	<0.03%	500	0.024X	372	279
Focus distance(min)		0.1m			450	0.026X	335.7	251.8
Flange back		17.526mm in air			400	0.029X	299.3	224.5
Back focus		13.8mm(min)			350	0.033X	263	197.2
Filter screw size		M27x0.5			300	0.039X	226.6	170
Front/Rear Effective Dia		Front ϕ 17.7mm Rear ϕ 8.65mm			250	0.046	190.2	142.7
Mount		C-Mount			200	0.057X	153.8	115.4
Temperature Range		-10~+50°C			150	0.075X	117.4	88
Storage Temperature Range		-20~+60°C			100	0.109X	80.7	60.3

TOLERANCE :
LINEARITY TOLERANCES \pm 0.05
ANGULAR TOLERANCES ARE \pm 30'
DRAFT ANGLES AREA \pm 0.5°/SIDE



材料(环保)

单位 比例

mm 2:1

设计						名称	2/3" 1000万 12mm	页码
校对								1/1
审核								版本
标记	处数	更改文件号	担当	变更日期	批准	代号	CSL-1228M	V2