



对焦固定手柄(整周3个均布)

光阑调节手柄(整周3个均布)

2/3" F2.8/35 C Mount				Working distance	Optical Magnification	2/3" Field of View(mm)		
Focal Length		f=35mm		mm		H	V	
Max Diameter (Ratio)		F=1:2.8~16		5000	0.007X	1253	940	
Picture Size		2/3"(8.8×6.6mm)	1/2"(6.4×4.8mm)	1/3"(4.8×3.6mm)	2000	0.018X	501.6	376.2
Angle \triangle	H	13.1°	9.5°	7.2°	1000	0.035X	251.1	188.4
	V	9.9°	7.2°	5.5°	900	0.039X	226.1	169.6
	D	16.3°	11.9°	8.8°	800	0.044X	201	150.8
Object Dimension at WD:200 \triangle	H	50.7mm	36.8mm	27.2mm	700	0.05X	176	132
	V	38mm	27.6mm	20.4mm	600	0.058X	150.9	113.2
	D	63.2mm	46mm	34mm	550	0.064X	138.4	103.8
Distortion (TV)		<0.1%	<0.05%	<0.03%	500	0.07X	125.9	94.4
Focus distance(min)		0.1m		450	0.078X	113.4	85	
Flange back		17.526mm in air		400	0.087X	100.8	75.6	
Back focus		16.55mm in air		350	0.1X	88.3	66.2	
Filter screw size		M27×0.5		300	0.116X	75.8	56.8	
Front/Rear Effective Dia		Front ϕ 16.8mm Rear ϕ 11mm		250	0.139X	63.2	47.4	
Mount		C-Mount		200	0.174X	50.7	38	
Temperature Range		-10~+50°C		150	0.231X	38.1	28.6	
Storage Temperature Range		-20~+60°C		100	0.347X	25.5	19.2	

				TOLERANCE: LINEARITY TOLERANCES ± 0.05 ANGULAR TOLERANCES ARE $\pm 30'$ DRAFT ANGLES AREA $\pm 0.5^\circ$ /SIDE		三角法		材料(环保)		单位	比例
								---		mm	2:1
				设计				名称		2/3" 1000万 35mm	
				2018-05-08 校对				代号		CSL-3528M	
				2018-03-13 审核						页码	
				2018-03-13 审核						1/1	
				2018-03-13 审核						版本	
				2018-03-13 审核						V2	
标记	处数	更改文件号	担当	变更日期	批准						